

4" Lo-Watt™ Range

The Lo-Watt range of wall fans can dramatically reduce power consumptions by using a DC motor which uses less energy compared to a normal fan.

Cat No.	Product Type
LW100S	Lo Watt standard fan
LW100T	Lo Watt Timer Fan incorporating a 1-20 mins over run
LW100H	Lo Watt Humidity & Timer Fan incorporating a 1-20 mins over run and adjustable humidistat 20-90% RH

Safety Extra Low voltage (SELV) includes fan and transformer

SELVLW100S	Lo Watt standard fan
SELVLW100T	Lo Watt Timer Fan incorporating a 1-20 mins over run
SELVLW100H	Lo Watt Humidity & Timer Fan incorporating a 1-20 mins over run and adjustable humidistat 20-90% RH

Additional Information

Maximum pressure:	50 p.a.
Fan speed :	2400 r.p.m.
Sound Volume :	40 dB(A)
Maximum operating temperature:	40 °C
Maximum Airflow l/s:	21.5
Power Consumption (Watts):	6.2



**SFP Down To
0.29**

4" Axial Fan Range

Designed for wall or ceiling mounting, this comprehensive range offers a wide selection of quiet and efficient models for use in bathrooms and Toilets. Comes complete with a backdraught shutter.

Cat No.	Product Type
LXF100S	Standard model for remote switching
LXF100P	As above supplied with pullcord switch
LXF100T	Timer model incorporating integral adjustable electronic timer (1-20 mins)
LXF100H	Humidity control which is adjustable between 40% RH and 95% RH complete with integral adjustable timer (1-20 mins)
LXF100PIR	PIR activated model which switches on as a person enters the room and runs on after the room is vacated. There is no need to connect to a separate switch timer adjustable between 1-20mins. Requires no switched live.

Additional Information

Maximum pressure:	20 p.a.
Fan speed :	2400 r.p.m.
Sound Volume :	41.0 dB(A)
Maximum operating temperature:	40 °C
Maximum Airflow l/s:	25.5
Power Consumption (Watts):	10.77



**SFP Down To
0.42**

6" Axial Fan Range

Designed for wall or ceiling mounting, the Efficient and easy to install range offers an alternative style and design to the traditional 6" Kitchen style. Comes complete with a backdraught shutter.

Cat No.	Product Type
LXF150BS	Standard model for remote switching
LXF150BP	As above supplied with pullcord switch
LXF150BT	Timer model incorporating integral adjustable electronic timer (1-20 mins)
LXF150BH	Humidity control which is adjustable between 40% RH and 95% RH complete with integral adjustable timer (1-20 mins)
LXF150BPIR	PIR activated model which switches on as a person enters the room and runs on after the room is vacated. There is no need to connect to a separate switch timer adjustable between 1-20mins. Requires no switched live.

Additional Information

Maximum pressure:	50 p.a.
Fan speed :	2400 r.p.m.
Sound Volume :	40 dB(A)
Maximum operating temperature:	40 °C
Maximum Airflow l/s:	64
Power Consumption (Watts):	18



**SFP Down To
0.28**

MANROSE™